



1. Identification of the substance/mixture and of the company/undertaking

Product name 1009S Super Green Powdered Pearl

Product code 1009S

Intended use of the substance/preparation

Pigment used in coating manufacturing (for professional use)

Company/Undertaking Identification

Producer/Supplier DuPont Australia Ltd
Street/Box 7 Eden Park Drive
Nat.-Code/Postal code/City Macquarie Park NSW 2113, Australia
Telephone (02) 9923 6111
Telefax (02) 9923 6011

Product Information

Telephone (02) 9923 6111

Emergency Information

Medical Emergency Phone 1800 674 415
Transportation Emergency Phone (02) 9923 6275

For further information, please also consult our Internet site

<http://www.dupont.com>

2. Hazards identification

Non-Hazardous Substance. Non-Dangerous Goods.

Human health hazards

Classification : Flammable;
Flammable.

Special hazard instructions for humans and environment

Do not breathe dust. Use only in well-ventilated areas.

3. Composition/information on ingredients

Chemical characterization

Pigment

Hazardous components

CAS-No.	Chemical Name	Concentration	Classification
64741-65-7	naphtha (petroleum), heavy alkylate (<0,1% benzene)	10.00 - < 12.50 %	R53 Xn; R65 R66 NotaH

Additional advice

See full text of R-phrases in chapter 16.

4. First aid measures

General advice

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Skin contact**

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

5. Fire-fighting measures

Hazardous combustion products

Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Exposure to decomposition products may be a hazard to health.

Fire and Explosion Hazards

no data available

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

Additional advice

Cool closed containers exposed to fire with water spray.

Additional information

Hazchem :

6. Accidental release measures

Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Comply with the health and safety at work laws. If material is a coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

**Advice on protection against fire and explosion**

Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Storage**Requirements for storage areas and containers**

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

8. Exposure controls/personal protection

Additional technical information on the plant

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

National occupational exposure limits

CAS-No.	Chemical Name	Values	Control Parameters	Basis
64741-65-7	naphtha (petroleum), heavy alkylate (<0,1% benzene)			no exposure standard allocated

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Glove material	Glove thickness	Break through time
Nitrile rubber	0.33 mm	60 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Eye protection

Use safety eyewear designed to protect against splash of products.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

Environmental exposure controls

Do not let product enter drains. For ecological information refer to section 12.

9. Physical and chemical properties

**Appearance**

Form: liquid Colour: pearl

Important physical and chemical information

	Value	Method
Flash point	Not applicable.	
Ignition temperature	355 °C	DIN 51794
Boiling point/boiling range	Not applicable.	
Lower explosion limit	Not applicable.	
Upper explosion limit	Not applicable.	
Vapour pressure	0.1 hPa	
Relative density	2.59 g/cm ³	DIN 53217/ISO 2811
Water solubility	nil	
Viscosity (23 °C)	Not applicable.	ISO 2431-1993
Solvent separation test	< 3%	ADR/RID
Content of volatile components (including water)	10.0%	Basis Vapour pressure >= 0.01 kPa
pH	Not applicable.	

Does not sustain combustion.

10. Stability and reactivity**Stability**

Stable

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information**General observations**

There is no data available on the product. See sections 3 and 15 for details.

Practical experience

Not applicable.

Toxicity Test Type	Value	Time	Species
naphtha (petroleum), heavy alkylate (<0,1% benzene)			
Oral LD50	> 2,000 mg/kg		rat
Dermal LD50	> 2,000 mg/kg		rabbit
Inhalation LC50	> 5 mg/l	4 h	rat

12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. Product does not contain organic linked halogens contributing to AOX.

Acute toxicity aquatic invertebrates

Chemical Name	Species	Type	Exposure time	Value	Method
naphtha (petroleum), heavy alkylate (<0,1% benzene)	Daphnia	EC50	72 h	1,000 mg/l	

**Acute and extended toxicity of fishes**

Chemical Name	Species	Type	Exposure time	Value	Method
naphtha (petroleum), heavy alkylate (<0,1% benzene)	Oncorhynchus mykiss (rainbow trout)	LC50	96 h	1,000 mg/l	

Mobility

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

13. Disposal considerations

Incinerate or otherwise dispose of waste material in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not incinerate in closed containers.

14. Transport information

Not classified as dangerous in the meaning of transport regulations.

15. Regulatory information**R-phrases(s)**

R10 | Flammable.

S-phrases(s)S22 | Do not breathe dust.
S51 | Use only in well-ventilated areas.**Standard for the Uniform Scheduling of Drugs and Poisons.**

No poison schedule number allocated.

16. Other information

Full text of R phrases with no. appearing in section 3

R53 | May cause long-term adverse effects in the aquatic environment.
R65 | Harmful: may cause lung damage if swallowed.
R66 | Repeated exposure may cause skin dryness or cracking.

Sources of key data used to compile the datasheet:

1. National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition (NOHSC:2011(2003))
2. Approved Criteria for Classifying Hazardous Substances (NOHSC:1008(1999))
3. List of Designated Hazardous Substances (NOHSC:10005(1999))
4. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment (NOHSC:1003(1995))
5. Australian Dangerous Goods Code, No. 6 (National Road Transport Commission)
6. Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP)
7. National Code of Practice for the Labelling of Workplace Substances ((NOHSC:2012 (1994))



Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Report version

Version	Changes
2.0	2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16

Revision Date: 2009-10-06