



## 1. Identification of the substance/mixture and of the company/undertaking

**Product name** 762R Hardener (For 769R)

**Product code** 762R

**Intended use of the substance/preparation**

Hardener for professional use

**Company/Undertaking Identification**

Producer/Supplier DuPont Australia Ltd  
Street/Box 7 Eden Park Drive  
Nat.-Code/Postal code/City Macquarie Park NSW 2113, Australia  
Telephone (02) 9923 6111  
Telefax (02) 9923 6011

**Product Information**

Telephone (02) 9923 6111

**Emergency Information**

Medical Emergency Phone 1800 674 415  
Transportation Emergency Phone (02) 9923 6275

**For further information, please also consult our Internet site**

<http://www.dupont.com>

## 2. Hazards identification

Hazardous Substance. Dangerous Goods.

**Human health hazards**

Classification : Irritant; Sensitising; Oxidising;  
Irritating to eyes. May cause sensitization by skin contact. May cause fire.

**Special hazard instructions for humans and environment**

Keep container tightly closed in a cool place. Wear suitable gloves and eye/face protection. If swallowed, seek medical advice immediately and show this container or label.

## 3. Composition/information on ingredients

**Chemical characterization**

Mixture of synthetic resins and solvents as well as water

**Hazardous components**

CAS-No.	Chemical Name	Concentration	Classification
94-36-0	dibenzoyl peroxide	45.00 - < 55.00 %	R43 Xi; R36 E; R2

**Additional advice**

See full text of R-phrases in chapter 16.

## 4. First aid measures

**General advice**

When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person.

**Inhalation**

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

**Skin contact**

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

**Ingestion**

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

## 5. Fire-fighting measures

**Hazardous combustion products**

Fire will produce dense black smoke containing hazardous combustion products (see heading 10). Exposure to decomposition products may be a hazard to health.

**Fire and Explosion Hazards**

no data available

**Suitable extinguishing media**

Water spray, Dry chemical, Foam.

**Extinguishing media which shall not be used for safety reasons**

High volume water jet

**Special Protective Equipment and Fire Fighting Procedures**

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

**Additional advice**

Cool closed containers exposed to fire with water spray.

**Additional information**

Hazchem : 1W

## 6. Accidental release measures

**Personal precautions**

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

**Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

**Methods for cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

## 7. Handling and storage

**Handling**

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

**Safe handling advice**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Comply with the health and safety at work laws. If material is a coating, do not sand, flame cut, braze or weld dry coating without an appropriate respirator or appropriate ventilation, and gloves.

**Advice on protection against fire and explosion**

Solvent vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

**Storage****Requirements for storage areas and containers**

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

**Advice on common storage**

Store separately from combustible materials, reducing agents (e.g. amines), acids, alkalis and heavy metal compounds (e.g. accelerators, driers, metal soaps)

## 8. Exposure controls/personal protection

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

**Additional technical information on the plant**

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**National occupational exposure limits**

CAS-No.	Chemical Name	Values	Control Parameters	Basis
94-36-0	dibenzoyl peroxide	TWA	5 mg/m <sup>3</sup>	NOHSC:1003(2003)

**Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

**Respiratory protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

**Hand protection**

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Glove material	Glove thickness	Break through time
Nitrile rubber	0.33 mm	60 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

**Eye protection**

Wear protective eyewear for protection against solvent spatter.

**Skin and body protection**

Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

**Hygiene measures**

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

**Environmental exposure controls**

Do not let product enter drains. For ecological information refer to section 12.



## 9. Physical and chemical properties

### Appearance

Form: liquid Colour: red

### Important physical and chemical information

	Value	Method
Flash point	Not applicable.	DIN 53213/ISO1523
Ignition temperature	Not applicable.	DIN 51794
Boiling point/boiling range	Not applicable.	
Lower explosion limit	Not applicable.	
Upper explosion limit	Not applicable.	
Vapour pressure	Not applicable.	
Relative density	1.1 g/cm <sup>3</sup>	DIN 53217/ISO 2811
Water solubility	appreciable	
Viscosity (23 °C)	60 s	ISO 2431-1993 6 mm
Solvent separation test	< 3%	ADR/RID
Content of volatile components (including water)	17.7%	Basis Vapour pressure >= 0.01 kPa
pH	Not applicable.	

## 10. Stability and reactivity

### Stability

Stable

### Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

### Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Store separately from combustible materials, reducing agents (e.g. amines), acids, alkalis and heavy metal compounds (e.g. accelerators, driers, metal soaps)

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, benzoic acid, benzene, diphenyl, phenylbenzoate; for cyclohexanone peroxides, hexane carbonic acid, lauric carbon acid, cyclohexane.

## 11. Toxicological information

### General observations

There is no data available on the product. See sections 3 and 15 for details.

### Practical experience

Contains dibenzoyl peroxide. May produce an allergic reaction.

Toxicity Test Type	Value	Time	Species
dibenzoyl peroxide			
Oral LD50	7,710 mg/kg		rat
Oral LD50	> 5,000 mg/kg		rat
Inhalation LD50	> 24.3 mg/l	4 h	rat

## 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses. Product does not contain organic linked halogens contributing to AOX.

### Mobility

No information available.

**Persistence and degradability**

No information available.

**Bioaccumulative potential**

No information available.

**13. Disposal considerations**

Incinerate or otherwise dispose of waste material in accordance with local regulations. The product should not be allowed to enter drains, water courses or the soil. Do not incinerate in closed containers.

**14. Transport information**

Transport in accordance with the requirements of the Carriage of Dangerous Goods by Road and Rail (Classifications, Packaging and Labeling), ADG for road, IMDG for sea and ICAO/IATA for air transport.

**ADG (Land transport)**

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID  
(dibenzoyl peroxide)  
UN-Number: 3108  
Hazard Class: 5.2  
Subsidiary Hazard Class: Not applicable.  
Packing group:  
Hazchem: 1W

**IMDG (Sea transport)**

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID  
(dibenzoyl peroxide)  
UN-Number: 3108  
Hazard Class: 5.2  
Subsidiary Hazard Class: Not applicable.  
Packing group:  
Marine Pollutant: N  
EmS: F-J,S-R

**ICAO/IATA (Air transport)**

Proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID  
(dibenzoyl peroxide)  
UN-Number: 3108  
Hazard Class: 5.2  
Subsidiary Hazard Class: Not applicable.  
Packing group:

**15. Regulatory information****Symbol and indication of hazard.**

Xi	Irritant
O	Oxidising
Contains	dibenzoyl peroxide 45.00 - < 55.00 %.

**R-phrases(s)**

R36	Irritating to eyes.
R43	May cause sensitization by skin contact.
R7	May cause fire.

**S-phrases(s)**

S3/7	Keep container tightly closed in a cool place.
S37/39	Wear suitable gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.

**Standard for the Uniform Scheduling of Drugs and Poisons.**

No poison schedule number allocated.

**16. Other information**

Full text of R phrases with no. appearing in section 3

R2	Risk of explosion by shock, friction, fire or other sources of ignition.
R36	Irritating to eyes.
R43	May cause sensitization by skin contact.

Sources of key data used to compile the datasheet:

1. National Code of Practice for the Preparation of Material Safety Data Sheets 2nd Edition (NOHSC:2011(2003))
2. Approved Criteria for Classifying Hazardous Substances (NOHSC:1008(1999))
3. List of Designated Hazardous Substances (NOHSC:10005(1999))
4. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment (NOHSC:1003(1995))
5. Australian Dangerous Goods Code, No. 6 (National Road Transport Commission)
6. Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP)
7. National Code of Practice for the Labelling of Workplace Substances ((NOHSC:2012 (1994))

**Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Report version**

Version	Changes
5.0	2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16

Revision Date: 2009-10-15