

1. Identification of the substance/mixture and of the company/undertaking

Product name	800RA Plastic Adhesion Promotor Spray
Product code	800RA
Intended use of the substance/preparation	Coating for professional use
Supplier	Du Pont (New Zealand) Limited
Street address	Central Park Corporate Centre Level 2, Building 5 666 Great South Road Greenlane, Auckland 1051
Telephone	(64)-9526 2501
Telefax	(64)-9526 2505
Emergency telephone number	NZ Poisons Information Centre Ph: 0800 764 766 24-hour Emergency Number: (64)-9526 2501
Date of preparation	2011-06-01

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

Acute oral toxicity	Category 6.1E
Serious eye damage/eye irritation	Category 6.4A
Carcinogenicity	Category 6.7B
Toxicity for reproduction	Category 6.8B
Acute aquatic toxicity	Category 9.1B
Chronic aquatic toxicity	Category 9.1C
Ecotoxic to terrestrial invertebrates	Category 9.4C

Endpoints which are "not classified", "cannot classified" and "not applicable" are not shown

GHS-Labeling

Hazard symbols



Signal word

Warning

Hazard statements

May be harmful if swallowed.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
Suspected of causing cancer.
Toxic to aquatic life.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Wear eye/face protection.
Avoid release to the environment.
Obtain special instructions before use.
IF exposed or concerned: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Wash hands after handling.
Store locked up.
Dispose of contents/container in accordance with local regulation.

**Other hazards which do not result in classification**

Contains epoxy constituents. See information supplied by the manufacturer. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

3. Composition/information on ingredients**Pure substance/mixture**

Mixture

CAS-No.	Chemical Name	Concentration	GHS ardous	Haz-
1330-20-7	xylene	40 - 50%	✓	
115-10-6	dimethyl ether	20 - 30%	✓	
100-41-4	ethylbenzene	10 - 20%	✓	
123-86-4	n-butyl acetate	0.3 - 1.0%	✓	
61789-01-3	Fatty acid, tall oil	0.3 - 1.0%	✓	
872-50-4	N-methyl-2-pyrrolidone	0.3 - 1.0%	✓	
108-88-3	toluene	0.3 - 1.0%	✓	
108-90-7	chlorobenzene	0.1 - 0.3%	✓	
818-61-1	2-hydroxyethyl acrylate	0.0 - 0.1%	✓	
79-10-7	acrylic acid	0.0 - 0.1%	✓	
71-43-2	benzene	0.0 - 0.1%	✓	
25068-38-6	epoxy resin (number average molecular weight <= 700)	0.0 - 0.1%	✓	
96-48-0	tetrahydrofuran-2-one	0.0 - 0.1%	✓	
75-21-8	ethylene oxide	0.0 - 0.1%	✓	
110-19-0	isobutyl acetate	0.0 - 0.1%	✓	
97-86-9	isobutyl methacrylate	0.0 - 0.1%	✓	
74-89-5	methylamine (mono-)	0.0 - 0.1%	✓	
80-62-6	methyl methacrylate	0.0 - 0.1%	✓	
71-36-3	n-butanol	0.0 - 0.1%	✓	
97-88-1	n-butyl methacrylate	0.0 - 0.1%	✓	
150-76-5	Phenol, 4-methoxy	0.0 - 0.1%	✓	

Non-regulated ingredients 5 - 10%

4. First aid measures**Eye contact**

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

**Inhalation**

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this container or label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed**Inhalation**

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Fire-fighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Specific hazards

Flammable liquid. Vapours may form explosive mixtures with air. Remove all sources of ignition. Do not allow run-off from fire fighting to enter drains or water courses.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

6. Accidental release measures

Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

**Storage****Suitable storage conditions**

Observe label precautions. Store between 5 and 25 °C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection**National occupational exposure limits
Workplace Exposure Standards (WESs) 2002**

Chemical Name		
xylene	TWA	50 ppm
	TWA	217 mg/m3
dimethyl ether	TWA	400 ppm
	TWA	766 mg/m3
	STEL	500 ppm
	STEL	958 mg/m3
ethylbenzene	TWA	100 ppm
	TWA	434 mg/m3
	STEL	125 ppm
	STEL	543 mg/m3
n-butyl acetate	TWA	150 ppm
	TWA	713 mg/m3
	STEL	200 ppm
	STEL	950 mg/m3
N-methyl-2-pyrrolidone	TWA	25 ppm
	TWA	103 mg/m3
	STEL	75 ppm
	STEL	309 mg/m3
toluene	TWA	50 ppm
	TWA	188 mg/m3
chlorobenzene	TWA	10 ppm
	TWA	46 mg/m3
acrylic acid	TWA	2 ppm
	TWA	5.9 mg/m3
benzene	TWA	5 ppm
	TWA	16 mg/m3
ethylene oxide	TWA	1 ppm
	TWA	1.8 mg/m3



Chemical Name

isobutyl acetate	TWA	150 ppm
	TWA	713 mg/m3
methylamine (mono-)	TWA	10 ppm
	TWA	13 mg/m3
methyl methacrylate	TWA	50 ppm
	TWA	208 mg/m3
	STEL	100 ppm
	STEL	416 mg/m3
n-butanol	CEIL	50 ppm
	CEIL	150 mg/m3
Phenol, 4-methoxy	TWA	5 mg/m3

Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Eye protection

Wear protective eyewear for protection against solvent spatter.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical Name	Glove material	Glove thickness	Break through time
xylene	Nitrile rubber	0.33 mm	30 min
	Viton (R) ®	0.7 mm	480 min
n-butyl acetate	Viton (R) ®	0.7 mm	10 min
	Nitrile rubber	0.33 mm	30 min
N-methyl-2-pyrrolidone	Nitrile rubber	0.33 mm	30 min
	Viton (R) ®	0.7 mm	60 min
n-butanol	Viton (R) ®	0.7 mm	480 min
	Nitrile rubber	0.33 mm	480 min

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatrill® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier



on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties

Appearance

Form : aerosol Colour: clear Odor Threshold : no data available

pH	not applicable	
Freezing point	Not applicable.	
Boiling point	-24 °C	
Flash point	-4 °C	
Evaporation rate	Slower than Ether	
Flammability		
Upper explosion limit	18.6 %	
Lower explosion limit	1 %	
Vapour pressure	305.2 hPa	
Solubility(ies)	partly miscible	
Vapour density	no data available	
Density	0.81 g/cm ³	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	no data available	
Ignition temperature	235 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	Not applicable.	ISO 2431-1993

10. Stability and reactivity

Stability

Stable

Hazardous polymerisation

Will not occur.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

**Skin or eye contact**

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:**Acute oral toxicity**

xylene	Category 5
ethylbenzene	Category 5
N-methyl-2-pyrrolidone	Category 5
toluene	Category 4
chlorobenzene	Category 4
2-hydroxyethyl acrylate	Category 3
acrylic acid	Category 4
tetrahydrofuran-2-one	Category 4
ethylene oxide	Category 3
isobutyl acetate	Category 5
methylamine (mono-)	Category 3
methyl methacrylate	Category 4
n-butanol	Category 4
Phenol, 4-methoxy	Category 4

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition 34.4 %

Serious eye damage/eye irritation

xylene	Category 2B
dimethyl ether	Category 2A
ethylbenzene	Category 2B
Fatty acid, tall oil	Category 1
N-methyl-2-pyrrolidone	Category 2A
toluene	Category 2A
chlorobenzene	Category 2A
2-hydroxyethyl acrylate	Category 1
acrylic acid	Category 1
benzene	Category 2A
epoxy resin (number average molecular weight <= 700)	Category 2B
tetrahydrofuran-2-one	Category 2A
ethylene oxide	Category 2A
isobutyl acetate	Category 2B
isobutyl methacrylate	Category 2A
methylamine (mono-)	Category 1
methyl methacrylate	Category 2A
n-butanol	Category 2A
n-butyl methacrylate	Category 2A
Phenol, 4-methoxy	Category 2A

Carcinogenicity

ethylbenzene	Category 2
benzene	Category 1A
ethylene oxide	Category 1A

Toxicity for reproduction

ethylbenzene	Category 2
N-methyl-2-pyrrolidone	Category 2
benzene	Category 2
ethylene oxide	Category 1A



methylamine (mono-) Category 2
methyl methacrylate Category 2

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorption, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

Product contains environmentally hazardous substances and product is classified per GHS.

Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute aquatic toxicity

xylene	Category 2
ethylbenzene	Category 1
n-butyl acetate	Category 3
toluene	Category 3
chlorobenzene	Category 1
2-hydroxyethyl acrylate	Category 1
acrylic acid	Category 1
benzene	Category 2
epoxy resin (number average molecular weight <= 700)	Category 1
tetrahydrofuran-2-one	Category 2
isobutyl acetate	Category 3
isobutyl methacrylate	Category 1
methylamine (mono-)	Category 3
methyl methacrylate	Category 3
n-butyl methacrylate	Category 3
Phenol, 4-methoxy	Category 1

Chronic aquatic toxicity

xylene	Category 3
ethylbenzene	Category 4
n-butyl acetate	Category 4
toluene	Category 4
chlorobenzene	Category 1
epoxy resin (number average molecular weight <= 700)	Category 1
tetrahydrofuran-2-one	Category 4
ethylene oxide	Category 4

Ecotoxic to terrestrial invertebrates

xylene Category 9.4C

% of unknown composition 35.4%

Persistence and degradability

No information available.

Bioaccumulation

No information available.

**Mobility in soil**

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with local regulations.

Disposal considerations

14. Transport information

NZS5433

Proper shipping name: AEROSOLS

UN number: 1950

Hazard Class: 2.1

Packing group:

Hazchem Code:

IMDG (Sea transport)

Proper shipping name: AEROSOLS

UN number: 1950

Hazard Class: 2.1

Subsidiary Hazard Class: Not applicable.

Packing group:

Marine Pollutant: no

EmS: F-D,S-U

ICAO/IATA (Air transport)

Proper shipping name: AEROSOLS, FLAMMABLE

UN number: 1950

Hazard Class: 2.1

Subsidiary Hazard Class: Not applicable.

Packing group:

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

National regulatory information

HSNO Approval Code	HSR002520
HSNO Classification	
Acute oral toxicity	Category 6.1E
Serious eye damage/eye irritation	Category 6.4A
Carcinogenicity	Category 6.7B
Toxicity for reproduction	Category 6.8B
Acute aquatic toxicity	Category 9.1B
Chronic aquatic toxicity	Category 9.1C
Ecotoxic to terrestrial invertebrates	Category 9.4C

16. Other information

Sources of key data used to compile the Safety Data Sheet
Department

Du Pont (New Zealand) Limited



SAFETY DATA SHEET

800RA v2.0
Revision Date: 2011-06-01
Print Date: 2011-06-01
en/NZ Page 10 - 10

Central Park Corporate Centre
Level 2, Building 5
666 Great South Road
Greenlane, Auckland 1051

Data Review Department
Issuing date

Regulatory Affairs
2011-06-01

Revision Note

Version	Changes
2.0	2, 3, 4, 5, 9, 11, 12, 13, 14, 15, 16

Revision Date: 2011-06-01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.